



Mail : contacts@gmo.fr – Site : www.gmo.fr
ZA du Landreau – 49610 Mozé-sur-Louet
Tel : 02.41.79.79.00 – Fax : 02.41.79.79.09

Lathe CAZENEUVE Broken HB 575 x 1500

<u>Distance between tip</u>	1 500 mm
<u>Tip height</u>	250 mm
<u>Diameter allowed above the bench</u>	575 mm
<u>Diameter allowed above the straggler</u>	525 mm
<u>Diameter allowed in the fractional</u>	750mm
<u>Total Width of Fracture</u>	235mm
<u>Width of the fracture in front of the hole tray</u>	170mm
<u>Diameter allowed above the carriage</u>	300 mm
<u>Bore Spindle</u>	51
<u>Taper of the tailstock</u>	CM5
<u>Maximum cross carriage stroke</u>	305 mm
<u>Number of spindle speed</u>	18
<u>Power</u>	10 Cv
<u>Spindle Speed</u>	de 32 à 2 500 tr/min
<u>Electrical cabinet</u>	
<u>Dimensions: L x W x H</u>	2905 x 1175 x 1345
<u>Weight</u>	2 050 Kg

Visu HEIDENHAIN

Bezel

Tool holder for multifix

Counter point

