GMO

Gortina Machines Outils

3849 NCAV

Mail: contacts@gmo.fr – Site: www.gmo.fr ZA du Landreau – 49610 Mozé-sur-Louet Tel: 02.41.79.79.00 – Fax: 02.41.79.79.09

Lathe SCULFORT

MAXICAP series

Type: 380 x 5000 NR

Distance between tips: 5000mm

Diameter above bench: 780mm

Diameter above carriage: 580mm

Diameter above the cross slide: 580mm

Diameter allowed in the break: 1160mm

Total width of gap: 400mm

Break width in front of hole plate: 225mm

Spindle drilled to: 80mm

Spindle taper: CM 5

Tailstock taper: CM 5

Width of bed: 575mm

Diameter of spindle at collar: 110mm

Maximum passage through fixed steady rest: 380mm

Maximum cross slide travel: 600mm

Maximum swivel slide travel: 200mm

Tailstock quill maximum travel: 250mm

Motor power: 17 HP

Number of steps obtained

Metric: 90

Wit work: 84

Thread range

Metric (mm): 0.25 to 280

With work (threads per inch): 0.25 to 112

Longitudinal feed extremes (mm): 0.025 to 11.2

Extreme values for transverse feeds (mm): 0.012 to 5.6

Approximate weight: 4700 kgs





