GMO

Gortina Machines Outils

3849 NCAV

Mail : contacts@gmo.fr – Site : www.gmo.fr ZA du Landreau – 49610 Mozé-sur-Louet Tel : 02.41.79.79.00 – Fax : 02.41.79.79.09

Lathe SCULFORT

Brand: SCULFORT

Series MAXICAP

Type: 380 x 5000 NR

Distance between tip: 5000mm

Diameter allowed above the bed: 780mm

Diameter allowed above the trolley: 580mm

Diameter allowed above the cross slide: 580mm

Diameter allowed in the fractional: 1160mm

Total width of the fracture: 400mm

Width of the fracture in front of the hole tray: 225mm

Drilled spindle: 80mm

Spindle taper: CM 5

Taper of the tailstock: CM 5

Bench width: 575mm

Diameter from pin to collar: 110mm

Maximum passage through the fixed bezel: 380mm

Maximum cross carriage stroke: 600mm

Maximum travel of the swivel carriage: 200mm

Maximum travel of the tailstock sheath: 250mm

Engine power: 17 CV

Number of steps obtained

Metric: 90

Withwork: 84

Thread Range

Metric (mm): 0.25 à 280

Withwork (Thumb Fillets): 0.25 à 112

Extreme values of longitudinal advances (mm): 0.025 at 11.2

Extreme values of transverse advances (mm): 0.012 at 5.6

Approximate weight: 4700 kgs





